



TROYER

15492BK-LL

LED PATH LIGHT

Made of sturdy, solid aluminum, Troyer's warm and inviting heritage details and timeless finishes create a classic outdoor silhouette. Combining farmhouse and industrial, this path light features touches like the trademark gooseneck that suspends the rustic shade and a unique ribbed glass accent at the top for additional light. This low-voltage path light includes a long-lasting LED bulb that will light up walkways and other outdoor living spaces for safety and security. Available in two classic finishes - Black or Oil Rubbed Bronze.

| DETAILS | |
|-----------|---------------------------------------|
| FINISH: | Black |
| MATERIAL: | Aluminum |
| GLASS: | Cased Opal |
| DIMMABLE: | YES - WITH MLV ON TRANSFORMER PRIMARY |

| DIMENSIONS | |
|------------|-----|
| WIDTH: | 7" |
| HEIGHT: | 26" |
| DEPTH: | 8 |
| WEIGHT: | 2lb |

| LIGHT SOURCE | |
|---------------------------|---------------------------------------|
| LIGHT SOURCE: | Socketed |
| LED NAME: | 00T5-27LED-1.5 |
| WATTAGE: | 1-1.50w T5 LED *Included |
| VOLTAGE: | 12v |
| VOLT AMPS: | 1.8 |
| LUMENS: | 150 |
| CRI: | 90 |
| INCANDESCENT EQUIVALENCY: | 1 x 25w |
| DIMMABLE: | YES - WITH MLV ON TRANSFORMER PRIMARY |
| TRANSFORMER REQUIRED: | Yes |

| MOUNTING | |
|------------|---------|
| LEAD WIRE: | 1 X 36" |

| SHIPPING | |
|----------------|------|
| CARTON LENGTH: | 10 |
| CARTON WIDTH: | 9.1 |
| CARTON HEIGHT: | 28.7 |
| CARTON WEIGHT: | 3 |

PRODUCT DETAILS:

- Angular lines, a bold finish and robust details create an industrial edge to add flair to any type of facade
- Wet Rated
- LED Bulbs carry a 3-year limited warranty
- 12V systems with LED bulbs consume less energy leading to lower electricity bills and a reduced carbon footprint
- The Hinkley Home Automation App allows you to control your landscape lights anytime, anywhere. You can turn dimmers on/off and adjust sliding brightness settings remotely.
- A wiring kit and ground spike are supplied
- Photometrics are based off bulb photometrics
- Add style and safety to outdoor walkways; place about 6 feet apart from one another