

# LUMACORE ACCENT SPOT LIGHT

## 15300SK-LMA27K

12V VARIABLE OUTPUT LED 2700K

Accentuate your home's architecture and highlight your landscape's natural beauty with a warm ambient glow. Hinkley's Variable Output LumaCORE™ LED Accent Lighting Systems are expertly designed to withstand the elements and provide complete control over wattage and beam spread.

DETAILS	
FINISH:	Satin Black
MATERIAL:	Aluminum
GLASS:	Frosted Lens
DIMMABLE:	No

DIMENSIONS	
WIDTH:	4.5"
HEIGHT:	4"
DEPTH:	4.5
WEIGHT:	1lb

LIGHT SOURCE	
LIGHT SOURCE:	LumaCore
LED NAME:	27G4SE-12W
WATTAGE:	12w, 8w, 5w,3w LumaCore LED *Included
VOLTAGE:	12v
VOLT AMPS:	12.4, 7.8, 5.3, 3.2
LUMENS:	750, 475, 350, 260
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 60w, 45w, 35w, 25w
DIMMABLE:	No

MOUNTING	
LEAD WIRE:	1 X 18"

SHIPPING	
CARTON LENGTH:	4.5
CARTON WIDTH:	9
CARTON HEIGHT:	9
CARTON WEIGHT:	2

### PRODUCT DETAILS:

- LumaCore Series products carry a lifetime limited warranty
- Highlight special areas of your landscape such as foliage, trees, and architectural environments
- LumaCORE combines three lenses, two light color choices, and four brightness options to enhance your outdoor living spaces
- Incorporates CREE LEDs with application performance tested by CREE
- Variable Output LumaCORE™ LED Engines have an approximate 40,000-hour lifespan
- Wet Rated
- Wattage settings include: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- 12V systems with LED bulbs consume less energy leading to lower electricity bills and a reduced carbon footprint

# HINKLEY

HINKLEY  
33000 Pin Oak Parkway  
Avon Lake, OH 44012

PHONE: (440) 653-5500  
Toll Free: 1 (800) 446-5539

[hinkley.com](http://hinkley.com)